

## LIST OF TABLES

TABLE NO.	TITLE	PAGE NO.
II.1	Volume of effluent from different industries	22
II.2	Average amount of solid waste from beam house operations	23
II.3	Characteristics of tannery waste water	24
II.4	Pollution load in conventional processing of leather	26
III.1	List of Materials used in the Present Study	39
III.2	Percentage of Water Absorption by Wet-Salted Raw Skins with Time	52
III.3	Fitment parameters of various samples fitted with logistic model equation	53
III.4	Raw Weights against Experimental and Conventional Sample Nos.	55
III.5	Soaking table for the Experimental samples	66
III.6	Generalized soaking (Proposed) process for 1000 kg's lot	74
III.7	Recipe Followed for Conventional Processing of Leather	76
III.8	Alum treatment in final soak liquors	113
III.9	Solar evaporation of filtered soak liquors	115
A.1	Total dissolved solids in soak liquors of different stages	149
A.2	Salinity (as NaCl) of different soak liquors	150
A.3	BOD <sub>5</sub> <sup>20</sup> value of different soak liquors	151

<b>A.4</b>	COD value of different soak liquors	<b>152</b>
<b>B.1</b>	Thickness and Length of the finished leathers	<b>154</b>
<b>B.2</b>	Shrinkage Temperature of the finished leathers	<b>155</b>
<b>B.3</b>	Water vapour permeability of the finished leathers	<b>156</b>
<b>B.4</b>	Tensile Strength and % Elongation at break of the finished leathers	<b>157</b>
<b>B.5</b>	Double- hole stitch tear strength of the finished leathers	<b>161</b>
<b>B.6</b>	Grain crack strength and ball-bursting strength of the finished leathers	<b>163</b>
<b>B.7</b>	Absorption of water of finished leathers: Kubelka method	<b>164</b>
<b>B.8</b>	Dry-rub and Wet-rub colour fastness of the finished	<b>166</b>
<b>B.9</b>	Volatile matter content in leather	<b>167</b>
<b>B.10</b>	Ash content in leather	<b>168</b>
<b>B.11</b>	Chloride (as NaCl ) content in leather	<b>169</b>
<b>B.12</b>	Total sulphate (as Na <sub>2</sub> SO <sub>4</sub> ) content in leather	<b>170</b>
<b>B.13</b>	Chromium (as Cr) content in leather	<b>171</b>
<b>B.14</b>	Average value of different physical and chemical properties of finished leathers	<b>172</b>